

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

(11)

EP 0 670 064 B1

(43) Date of publication:  
06.09.1995 Bulletin 1995/36

(51) Int. Cl. 7 :  
G06F 15/00, G06F 15/02,  
G06F 19/00

(21) Application number: 94901533.3

(86) International application number:  
PCT/US93/11111

(22) Date of filing: 16.11.1993

(87) International publication number:  
WO 94/11831 (26.05.1994 Gazette 1994/12)

(84) Designated Contracting States:  
DE DK ES FR GB IT NL SE

(30) Priority: 17.11.1992 US 977323

(72) Inventor: BROWN, Stephen, James  
Palo Alto, CA 94301 (US)

(74) Representative:  
Spall, Christopher John  
Barker Brettell,  
138 Hagley Road  
Edgbaston, Birmingham B16 9PW (GB)

(54) MODULAR MICROPROCESSOR-BASED HEALTH MONITORING SYSTEM

(87) This international application for which the EPO is a designated office has not been republished by the EPO according to article 158(1) EPC.

Cette demande internationale pour laquelle l'OEB est office désigné n'a pas été republiée par l'OEB en vertu de l'article 158(1) CBE.

Diese internationale Anmeldung, für die das EPA Bestimmungsamt ist, würde, gemäß Artikel 158(1) EPÜ, vom EPA nicht wieder veröffentlicht.

EP 0 670 064 B1

## D scription

[0001] This invention relates to self-care health monitoring system that enable a patient or other user to gather data important to a health management program and, if appropriate, provide that data to a healthcare professional.

[0002] Controlling or curing conditions of ill health generally involves both establishing a therapeutic program and monitoring the progress of the afflicted person. Based on that progress, decisions can be made as to altering therapy to achieve a cure or maintain the affliction or condition at a controlled level. Successfully treating certain health conditions calls for rather frequent monitoring and a relatively high degree of patient participation. For example, in order to establish and maintain a regimen for successful diabetes care, a diabetic should monitor his or her blood glucose level and record that information along with the date and time at which the monitoring took place. Since diet, exercise, and medication all affect blood glucose levels, a diabetic often must record data relating to those items of information along with blood glucose level so that the diabetic may more closely monitor his or her condition and, in addition, can provide information of value to the healthcare provider in determining both progress of the patient and detecting any need to change the patient's therapy program.

[0003] Advances in the field of electronics over the past several years have brought about significant changes in medical diagnostic and monitoring equipment, including arrangements for self-care monitoring of various chronic conditions. With respect to the control and monitoring of diabetes, relatively inexpensive and relatively easy-to-use blood glucose monitoring systems have become available that provide reliable information that allows a diabetic and his or her healthcare professional to establish, monitor and adjust a treatment plan (diet, exercise, and medication). More specifically, microprocessor-based blood glucose monitoring systems are being marketed which sense the glucose level of a blood sample that is applied to a reagent-impregnated region of a test strip that is inserted in the glucose monitor. When the monitoring sequence is complete, the blood glucose level is displayed by, for example, a liquid crystal display (LCD) unit.

[0004] Typically, currently available self-care blood glucose monitoring units include a calendar/clock circuit and a memory circuit that allows a number of blood glucose test results to be stored along with the date and time at which the monitoring occurred. The stored test results (blood glucose level and associated time and date) can be sequentially recalled for review by the blood glucose monitor user or a health professional by sequentially actuating a push button or other control provided on the monitor. In some commercially available devices, the average of the blood glucose results that are stored in the monitor (or the average of the results for a predetermined period of time, e.g., fourteen days) also is displayed during the recall sequence. Further, some self-care blood glucose monitors allow the user to tag the test result with an "event code" that can be used to organize the test results into categories. For example, a user might use a specific event code to identify test results obtained at particular times of the day, a different event code to identify a blood glucose reading obtained after a period of exercise, two additional event codes to identify blood glucose readings taken during hypoglycemia symptoms and hyperglycemia symptoms, etc. When event codes are provided and used, the event code typically is displayed with each recalled blood glucose test result.

[0005] Microprocessor-based blood glucose monitoring systems have advantages other than the capability of obtaining reliable blood glucose test results and storing a number of the results for later recall and review. By using low power microprocessor and memory circuits and powering the units with small, high capacity batteries (e.g., a single alkaline battery), extremely compact and light designs have been achieved that allow taking the blood glucose monitoring system to work, school, or anywhere else the user might go with people encountered by the user not becoming aware of the monitoring system. In addition, most microprocessor-based self-care blood glucose monitoring systems have a memory capacity that allows the system to be programmed by the manufacturer so that the monitor displays a sequence of instructions during any necessary calibration or system tests and during the blood glucose test sequence itself. In addition, the system monitors various system conditions during a blood glucose test (e.g., whether a test strip is properly inserted in the monitor and whether a sufficient amount of blood has been applied to the reagent impregnated portion of the strip) and if an error is detected generates an appropriate display (e.g., "retest"). A data port may be provided that allows test results stored in the memory of the microprocessor-based blood glucose monitoring system to be transferred to a data port (e.g., RS-232 connection) of a personal computer or other such device for subsequent analysis.

[0006] Microprocessor-based blood glucose monitoring systems are a significant advance over previously available self-care systems such as those requiring a diabetic to apply a blood sample to reagent activated portions of a test strip; wipe the blood sample from the test strip after a predetermined period of time; and, after a second predetermined period of time, determine blood glucose level by comparing the color of the reagent activated regions of the test strip with a color chart supplied by the test strip manufacturer. Despite what has been achieved, numerous drawbacks and disadvantages still exist. For example, establishing and maintaining diabetic healthcare often requires the diabetic to record additional data pertaining to medication, food intake, and exercise. However,

the event codes of currently available microprocessor blood glucose monitoring systems provide only limited capability for tagging and tracking blood glucose test results according to food intake and other relevant factors. For example, the event codes of currently available monitoring systems only allow the user to classify stored blood glucose readings in a manner that indicates blood glucose tests taken immediately after a heavy, light or normal meal. This method of recording information not only requires subjective judgment by the system user, but will not suffice in a situation in which successfully controlling the user's diabetes requires the recording and tracking of relatively accurate information relating to food intake, exercise, or medication (e.g., insulin dosage). An otherwise significant advantage of currently available blood glucose monitoring systems is lost when blood glucose test results must be recorded and tracked with quantitative information relating to medication, food intake, or exercise. Specifically, the system user must record the required information along with a time and date tagged blood glucose test result by, for example, writing the information in a log book.

[0007] The use of event codes to establish subcategories of blood glucose test results has an additional disadvantage or drawback. In particular, although alphanumeric display devices are typically used in currently available microprocessor-based blood glucose monitoring systems, the display units are limited to a single line of information having on the order of six characters. Moreover, since the systems include no provision for the user to enter alphanumeric information, any event codes that are used must be indicated on the display in a generic manner, e.g., displayed as "EVENT 1", "EVENT 2", etc. This limitation makes the system more difficult to use because the diabetic must either memorize his or her assignment of event codes or maintain a list that defines the event codes. The limited amount of data that can be displayed at any one time presents additional drawbacks and disadvantages. First, instructions and diagnostics that are displayed to the user when calibrating the system and using the system to obtain a blood glucose reading must be displayed a line at a time and in many cases, the information must be displayed in a cryptic manner.

[0008] The above-discussed display limitations and other aspects of currently available blood glucose monitoring systems is disadvantageous in yet another way. Little statistical information can be made available to the user. For example, in diabetic healthcare maintenance, changes or fluctuations that occur in blood glucose levels during a day, a week, or longer period can provide valuable information to a diabetic and/or his or her healthcare professional. As previously mentioned, currently available systems do not allow associating blood glucose test results with attendant quantitative information relating to medication, food intake, or other factors such as exercise that affect a person's blood glucose level at any particular point in time. Thus, currently available blood glucose monitoring systems have little or no capability for the generating and display of trend information that may be of significant value to a diabetic or the diabetic's healthcare professional.

[0009] Some currently available blood glucose monitoring systems provide a data port that can be interconnected with and transfer data to a personal computer (e.g., via an RS-232 connection). With such a system and a suitable programmed computer, the user can generate and display trend information or other data that may be useful in administering his or her treatment plan. Moreover, in such systems, data also can be transferred from the blood glucose monitoring system to a healthcare professional's computer either directly or remotely by telephone if both the blood glucose monitoring system (or computer) to which the data has been downloaded and the healthcare professional's computer are equipped with modems. Although such a data transfer provision allows a healthcare professional to analyze blood glucose data collected by a diabetic, this aspect of currently available blood glucose monitoring systems has not found widespread application. First, the downloading and subsequent analysis feature can only be used by system users that have ready access to a computer that is programmed with appropriate software and, in addition, have both the knowledge required to use the software (and the inclination to do so). This same problem exists with respect to data transfer to (and subsequent analysis by) a healthcare professional. Moreover, various manufacturers of systems that currently provide a data transfer feature do not use the same data format. Therefore, if a healthcare professional wishes to analyze data supplied by a number of different blood glucose monitoring systems, he or she must possess software for each of the systems and must learn to conduct the desired analyses with each software system.

[0010] The above-discussed disadvantages and drawbacks of microprocessor-based self-care health monitoring systems take on even greater significance with respect to children afflicted with diabetes, asthma and other chronic illnesses. In particular, a child's need for medication and other therapy changes as the child grows. Current microprocessor-based self-care health monitoring systems generally do not provide information that is timely and complete enough for a healthcare professional to recognize and avert problems before relatively severe symptoms develop. Too often, a need for a change in medication and/or other changes in therapeutic regimen is not detected until the child's condition worsens to the point that emergency room care is required.

[0011] Further, currently available microprocessor-based health monitoring systems have not been designed with children in mind. As previously mentioned, such devices are not configured for sufficient ease of use in situations in which it is desirable or necessary to record and track quantitative information that affects the physical condition of the system user (e.g., medication dosage administered by a diabetic and food intake). Children above

the age at which they are generally capable of obtaining blood samples and administering insulin or other medication generally can learn to use at least the basic blood glucose monitoring features of currently available microprocessor-based blood glucose monitoring systems. However, the currently available monitoring systems provide nothing in the way of motivation for a child to use the device and, in addition, include little or nothing that educates the child about his or her condition or treatment progress.

[0012] The lack of provision for the entering of alphanumeric data also can be a disadvantage. For example, currently available blood glucose monitoring systems do not allow the user or the healthcare professional to enter information into the system such as medication dosage and other instructions or data that is relevant to the user's self-care health program.

[0013] The above-discussed disadvantages and drawbacks of currently available microprocessor-based blood glucose monitoring systems also have been impediments to adopting the basic technology of the system for other healthcare situations in which establishing and maintaining an effective regimen for cure or control is dependent upon (or at least facilitated by) periodically monitoring a condition and recording that condition along with time and date tags and other information necessary or helpful in establishing and maintaining a healthcare program.

[0014] In accordance with the system of the invention, a self-care health monitoring system is provided comprising a handheld programmable microprocessor-based unit, said programmable microprocessor-based unit including a display screen and a plurality of switches, said microprocessor-based unit being connectable in signal communication with a program cartridge or other arrangement that provides program instructions for controlling the operation of said programmable microprocessor-based unit,

monitoring means operable for automatically sensing a condition indicative of a person's physical well-being and for producing digitally encoded signals representative of said condition; and

a microprocessor-based data management unit connectable in signal communication with both said programmable microprocessor-based unit and said monitoring means, said microprocessor-based data management unit including a central processing unit and a memory circuit, said memory circuit for storing program instructions for controlling the operation of said central processing unit, said central processing unit being responsive to program instructions stored in said memory circuit of said microprocessor-based data management unit for processing said digitally encoded signals supplied by said monitoring means that are representative of said automatically sensed condition, said central processing unit of said data management unit supplying signals representative of said sensed condition to said programmable microprocessor-based unit in response to digitally encoded signals that are supplied to said data management unit by said programmable microprocessor-based unit upon selective operation of at least one of said switches of said programmable microprocessor unit, and in which the switches of the handheld programmable microprocessor-based unit, in operation, are used to select the operating mode of both said data management unit and said handheld microprocessor-based unit.

[0015] The system according to the invention provides a new and useful system for healthcare maintenance in which the invention either serves as a peripheral device to (or incorporates) a small handheld microprocessor-based unit of the type that includes a display screen, buttons or keys that allow a user to control the operation of the device and a program cartridge or other arrangement that can be inserted in the device to adapt the device to a particular application or function. The system according to the invention in effect converts the handheld microprocessor device into a healthcare monitoring system that has significant advantages over systems such as the currently available blood glucose monitoring systems. To perform this conversion, the invention includes a microprocessor-based healthcare data management unit, a program cartridge and a monitoring unit. When inserted in the handheld microprocessor unit, the program cartridge provides the software necessary (program instructions) to program the handheld microprocessor unit for operation with the microprocessor-based data management unit. Signal communication between the data management unit and the handheld microprocessor unit is established by an interface cable. A second interface cable can be used to establish signal communication between the data management unit and the monitoring unit or, alternatively, the monitoring unit can be constructed as a plug-in unit having an electrical connector that mates with a connector mounted within a region that is configured for receiving the monitoring unit.

[0016] In operation, the control buttons or keys of the handheld microprocessor-based unit are used to select the operating mode for both the data management unit and the handheld microprocessor-based unit. In response to signals generated by the control buttons or keys, the data management unit generates signals that are coupled to the handheld microprocessor unit and, under control of the program instructions contained in the program cartridge, establish an appropriate screen display on the handheld microprocessor-based unit display. In selecting system operating mode and other operations, the control buttons are used to position a cursor or other indicator in a

manner that allows the system user to easily select a desired operating mode or function and provide any other required operator input. In the disclosed detailed embodiment of the invention several modes of operation are made available.

[0017] In the currently preferred embodiments of the invention, the handheld microprocessor unit is a compact video game system such as the system manufactured by Nintendo of America Inc. under the trademark "GAME BOY." Use of a compact video game system has several general advantages, including the widespread availability and low cost of such systems. Further, such systems include switch arrangements that are easily adapted for use in the invention and the display units of such systems are of a size and resolution that can advantageously be employed in the practice of the invention. In addition, such systems allow educational or motivational material to be displayed to the system user, with the material being included in the program cartridge that provides the monitor system software or, alternatively, in a separate program cartridge.

[0018] The use of a compact video game system for the handheld microprocessorbased unit provided in the system of the invention is especially advantageous with respect to children. Specifically, the compact video game systems of the type that can be employed in the practice of the invention are well known and well accepted by children. Such devices are easily operated by a child and most children are well accustomed to using the devices in the context of playing video games. Motivational and educational material relating to the use of the invention can be presented in game-like or animated format to further enhance acceptance and use of the invention by children that require self-care health monitoring.

[0019] A microprocessor-based health monitoring system that is configured in accordance with the invention provides additional advantages for both the user and a healthcare professional. In accordance with one embodiment of the invention, standardized reports are provided to a physician or other healthcare provider by means of facsimile transmission. To accomplish this, the data management unit of the currently preferred embodiments of the invention include a modem which allows test results and other data stored in system memory to be transmitted to a remote clearinghouse via a telephone connection. Data processing arrangements included in the clearinghouse perform any required additional data processing; format the standardized reports; and, transmit the reports to the facsimile machine of the appropriate healthcare professional.

[0020] The clearinghouse also can fill an additional communication need, allowing information such as changes in medication dosage or other information such as modification in the user's monitoring schedule to be electronically sent to a system user. In arrangements that incorporate this particular aspect of the invention, information can be sent to the user via a telephone connection and the data management unit modem when a specific inquiry is initiated by the user, or when the user establishes a telephone connection with the clearinghouse for other purposes such as providing data for standardized reports.

[0021] The clearinghouse-facsimile aspect of the invention is important because it allows a healthcare professional to receive timely information about patient condition and progress without requiring a visit by the patient (system user) and without requiring analysis or processing of test data by the healthcare professional. In this regard, the healthcare professional need not possess or even know how to use a computer and/or the software conventionally employed for analysis of blood glucose and other health monitoring data and information.

[0022] The invention also includes provision for data analysis and memory storage of information provided by the user and/or the healthcare professional. In particular, the data management units of the currently preferred embodiments of the invention include a data port such as an RS-232 connection that allows the system user or healthcare professional to establish signal communication between the data management unit and a personal computer or other data processing arrangement. Blood glucose test data or other information can then be downloaded for analysis and recordkeeping purposes. Alternatively, information such as changes in the user's treatment and monitoring regimen can be entered into system memory. Moreover, if desired, remote communication between the data management unit and the healthcare professional's computer can be established using the clearinghouse as an element of the communications link. That is, in the currently preferred arrangements of the invention a healthcare professional has the option of using a personal computer that communicates with the clearinghouse via a modem and telephone line for purposes of transmitting instructions and information to a selected user of the system and/or obtaining user test data and information for subsequent analysis.

#### Brief Description of the Drawings

[0023] The foregoing aspects and many of the attendant advantages of this invention will become more readily appreciated as the same becomes better understood by reference to the following detailed description, when taken in conjunction with the accompanying drawings, wherein:

FIGURE 1 is a block diagram that illustrates a healthcare monitoring system arranged in accordance with the invention;

FIGURE 2 diagrammatically illustrates monitoring systems constructed in accordance with the invention connected in signal communication with a remotely located computing facility which includes provision for making the data supplied by the monitoring system of the invention available to a designated healthcare professional and/or for providing data and instructions to the system user;

FIGURE 3 is a block diagram diagrammatically depicting the structural arrangement of the system data management unit and its interconnection with other components of the system shown in FIGURE 1; and

FIGURES 4-10 depict typical system screen displays of data and information that can be provided by the arrangements shown in FIGURES 1-3.

#### Detailed Description

**[0024]** FIGURE 1 depicts a self-care health monitoring system arranged in accordance with the invention. In the arrangement shown in FIGURE 1, a data management unit 10 is electrically interconnected with a handheld microprocessor-based unit 12 via a cable 14. In the depicted arrangement, data management unit 10 also is electrically interconnected with a blood glucose monitor 16 of the type capable of sensing blood glucose level and producing an electrical signal representative thereof. Although FIGURE 1 illustrates blood glucose monitor 16 as being connected to data management unit 10 by a cable 18, it may be preferable to construct blood glucose monitor 16 as a plug-in unit that is placed in a recess or other suitable opening or slot in data management unit 10. Regardless of the manner in which blood glucose monitor 16 is interconnected with data management unit 10, both that interconnection and cable 14 are configured for serial data communication between the interconnected devices.

**[0025]** Also shown in FIGURE 1 are two additional monitoring devices 20 and 22, which are electrically connected for serial data communication with data management unit 10 via cables 24 and 26, respectively. Monitoring units 20 and 22 of FIGURE 1 represent devices other than blood glucose monitor 16 that can be used to configure the invention for self-care health monitoring applications other than (or in addition to) diabetes care. For example, as is indicated in FIGURE 1, the monitoring device 20 can be a peak-flow meter that provides a digital signal representative of the airflow that results when a person suffering from asthma or another chronic respiratory affliction expels a breath of air through the meter. As is indicated by monitor 22 of FIGURE 1, various other devices can be provided for monitoring conditions such as blood pressure, pulse, and body temperature to thereby realize systems for self-care monitoring and control of conditions such as hypertension, certain heart conditions and various other afflictions and physical conditions. Upon understanding the hereinafter discussed features of the invention it will be recognized that the system of the invention is easily implemented for these and other types of healthcare monitoring. In particular, monitors used in the practice of the invention can be arranged in a variety of ways as long as the data to be recorded or otherwise employed by handheld microprocessor unit 12 and/or data management unit 10 is provided in serial format in synchronization with clock signals provided by data management unit 10. As is the case with blood glucose monitor 16, the additional monitors can be configured as plug-in units that are directly received by data management unit 10, or can be connected to data management unit 10 with cables (as shown in FIGURE 1).

**[0026]** As is shown in FIGURE 1, handheld microprocessor unit 12 includes a display screen 28 and a plurality of switches or keys (30, 32, 34, 36, and 38 in FIGURE 1), which are mounted on a housing 40. Located in the interior of housing 40, but not shown in FIGURE 1, are a microprocessor, memory circuits, and circuitry that interfaces switches 30, 32, 34, 36 and 38 with the microprocessor. Stored in the memory of program handheld microprocessor unit 12 is a set of program instructions that establishes a data protocol that allows handheld microprocessor unit 12 to perform digital data signal processing and generate desired data or graphics for display on display unit 28 when a program cartridge 42 is inserted in a slot or other receptacle in housing 40. That is, program cartridge 42 of FIGURE 1 includes read-only memory units (or other memory means such as battery-powered random access memory) which store program instructions and data that adapt handheld microprocessor 12 for operation in a blood glucose monitoring system. More specifically, when the instructions and data of program cartridge 42 are combined with program instructions and data included in the internal memory circuits of handheld microprocessor unit 12, handheld microprocessor unit 12 is programmed for processing and displaying blood glucose information in the manner described below and additional monitors 22 to provide health monitoring for asthma and various other previously mentioned chronic conditions. In each case, the plurality of switches or keys (30, 32, 34, 36, and 38 in FIGURE 1) are selectively operated to provide signals that result in pictorial and/or alphanumeric information being displayed by display unit 42.

**[0027]** Various devices are known that meet the above-set forth description of handheld microprocessor unit 12.

For example, compact devices are available in which the plurality of keys allows alphanumeric entry and internal memory is provided for storing information such as names, addresses, phone numbers, and an appointment calendar. Small program cartridges or cards can be inserted in these devices to program the device for various purposes such as the playing of games, spreadsheet application, and foreign language translation sufficient for use in travel.

5 More recently, less compact products that have more extensive computational capability and are generally called "palm top computers" have been introduced into the marketplace. These devices also can include provision for programming the device by means of an insertable program card or cartridge.

[0028] The currently preferred embodiments of the invention are configured and arranged to operate in conjunction with yet another type of handheld microprocessor unit. Specifically, in the currently preferred  
10 embodiments of the invention, program cartridge 42 is electrically and physically compatible with commercially available compact video game systems, such as the system manufactured by Nintendo of America Inc. under the trademark "GAME BOY." Configuring data management unit 10 and program cartridge 42 for operation with a handheld video game system has several advantages. For example, the display unit of such a device provides display resolution that allows the invention to display both multi-line alphanumeric information and graphical data. In this regard,  
15 the 160 x 144 pixel dot matrix-type liquid crystal display screen currently used in the above-referenced compact video game systems provides sufficient resolution for at least six lines of alphanumeric text, as well as allowing graphical representation of statistical data such as graphical representation of blood glucose test results for a day, a week, or longer.

[0029] Another advantage of realizing handheld microprocessor unit 12 in the form of a compact video game system is the relatively simple, yet versatile arrangement of switches that is provided by such a device. For example, as is indicated in FIGURE 1, a compact video game system includes a control pad 30 that allows an object  
20 displayed on display unit 42 to be moved in a selected direction (i.e., up-down or left-right). As also is indicated in FIGURE 1, compact video game systems typically provide two pair of distinctly-shaped push button switches. In the arrangement shown in FIGURE 1, a pair of spaced-apart circular push button switches (36 and 38) and a pair of elongate switches (32 and 34) are provided. The functions performed by the two pairs of switches is dependent upon  
25 the program instructions contained in each program cartridge 42.

[0030] Yet another advantage of utilizing a compact video game system for handheld microprocessor-based unit 12 of FIGURE 1 is the widespread popularity and low cost of such units. In this regard, manufacture and sale of a data management unit 10, blood glucose monitor 16 and program cartridge 42 that operate in conjunction with a compact  
30 microprocessor-based video allows the self-care health monitoring system of FIGURE 1 to be manufactured and sold at a lower cost than could be realized in an arrangement in which handheld unit 12 is designed and manufactured solely for use in the system of FIGURE 1.

[0031] An even further advantage of using a compact video game system for handheld microprocessor 12 is that such video game systems include means for easily establishing the electrical interconnection provided by cable 14 in  
35 FIGURE 1. In particular, such compact video game systems include a connector mounted to the game unit housing (40 in FIGURE 1) and a cable that can be connected between the connectors of two video game units to allow interactive operation of the two interconnected units (i.e., to allow contemporaneous game play by two players or competition between players as they individually play identical but separate games) In the preferred embodiments of the invention, the "two-player" cable supplied with the compact video game unit being used as handheld microprocessor  
40 unit 12 is used as cable 14 to establish serial data communication between the handheld microprocessor unit 12 (compact video game system) and data management unit 10. In these preferred embodiments, the program instructions stored on the memory of data management unit 10 and program cartridge 42 respectively program data management unit 10 and the compact video game system (i.e., handheld microprocessor unit 12) for interactive operation in which switches 30, 32, 34, 36 and 38 are used to control the operation of data management unit 10 (e.g., to select a particular operational mode such as performance of a blood glucose test or the display of statistical test data and,  
45 in addition, to control operation such as selection of an option during operation of the system in a particular operational mode). In each operational mode, data management unit 10 processes data in accordance with program instructions stored in the memory circuits of data management unit 10. Depending upon the operational mode selected by the user, data is supplied to data management unit 10 by blood glucose monitor 16, by additional monitors (20 and 22 in FIGURE 1) or any interconnected computers or data processing facility (such as the hereinafter described user's computer 48 and clearinghouse 54 of FIGURE 1). During such operation, mode switches 30, 32, 34, 36 and 38  
50 are selectively activated so that signals are selectively coupled to the video game system (handheld microprocessor unit 12) and processed in accordance with program instructions stored in program cartridge 42. The signal processing performed by handheld microprocessor unit 12 results in the display of alphanumeric, symbolic, or graphic information on the video game display screen (i.e., display unit 28 in FIGURE 1), which allow the user to control  
55 system operation and obtain desired test results and other information.

[0032] Although the above-discussed advantages apply to use of the invention by all age groups, employing a compact video game system in the practice of the invention is of special significance in monitoring a child's blood

glucose or other health parameters. Children and young adults are familiar with compact video game systems. Thus, children will accept a health monitoring system incorporating a compact video game system more readily than a traditional system, even an embodiment of the invention that uses a different type of handheld microprocessor unit. Moreover, an embodiment of the invention that functions in conjunction with a compact video game system can be arranged to motivate children to monitor themselves more closely than they might otherwise by incorporating game-like features and/or animation in system instruction and test result displays. Similarly, the program instructions can be included in program cartridges 41, 42 and 43 (or additional cartridges) that allow children to select game-like displays that help educate the child about his or her condition and the need for monitoring.

**[0033]** With continued reference to FIGURE 1, data management unit 10 of the currently preferred embodiments of the invention includes a data port 44 that allows communication between data management unit 10 and a personal computer 48 (or other programmable data processor). In the currently preferred embodiments of the invention, data port 44 is an RS-232 connection that allows serial data communication between data management unit 10 and personal computer 48. In the practice of the invention, personal computer 48 can be used to supplement data management unit 10 by, for example, performing more complex analyses of blood glucose and other data that has been supplied to and stored in the memory circuits of data management unit 10. With respect to embodiments of the invention configured for use by a child, personal computer 48 can be used by a parent or guardian to review and analyze the child's progress and to produce printed records for subsequent review by a healthcare professional. Alternatively, personal computer 48 can be used to supply data to data management unit 10 that is not conveniently supplied by using handheld microprocessor switches 30, 32, 34, 36 and 38 as an operator interface to the system shown in FIGURE 1. For example, some embodiments of the invention may employ a substantial amount of alphanumeric information that must be entered by the system user. Although it is possible to enter such data by using switches 30, 32, 34, 36 and 38 in conjunction with menus and selection screens displayed on display screen 28 of FIGURE 1, it may be more advantageous to use a device such as personal computer 48 for entry of such data. However, if personal computer 48 is used in this manner, some trade-off of system features may be required because data management unit 10 must be temporarily interconnected with personal computer 48 during these operations. That is, some loss of system mobility might result because a suitably programmed personal computer would be needed at each location at which data entry or analysis is to occur.

**[0034]** As is indicated in FIGURE 1, data management unit 10 of the currently preferred embodiments of the invention also includes a modem that allows data communication between data management unit 10 and a remote computing facility identified in FIGURE 1 as clearinghouse 54 via a conventional telephone line (indicated by reference numeral 50 in FIGURE 1) and a modem 52 that interconnects clearinghouse 54 and telephone line 50. As shall be described in more detail, clearinghouse computing facility 54 facilitates communication between a user of the system shown in FIGURE 1 and his or her healthcare professional and can provide additional services such as updating system software. As is indicated by facsimile machine 55 of FIGURE 1, a primary function of clearinghouse 54 is providing the healthcare professional with standardized reports 56, which indicate both the current condition and condition trends of the system user. Although a single facsimile machine 55 is shown in FIGURE 1, it will be recognized that numerous healthcare professionals (and hence facsimile machine 55) can be connected in signal communication with a clearinghouse 54.

**[0035]** Regardless of whether a compact video game system, another type of commercially available handheld microprocessor-based unit, or a specially designed unit is used, the preferred embodiments of FIGURE 1 provide a self-care blood glucose monitoring system in which program cartridge 42: (a) adapts handheld microprocessor unit 12 for displaying instructions for performing the blood glucose test sequence and associated calibration and test procedures; (b) adapts handheld microprocessor unit 12 for displaying (graphically or alphanumerically) statistical data such as blood glucose test results taken during a specific period of time (e.g., a day, week, etc.); (c) adapts handheld microprocessor unit 12 for supplying control signals and signals representative of food intake or other useful information to data management unit 10; (d) adapts handheld microprocessor unit 12 for simultaneous graphical display of blood glucose levels with information such as food intake; and, (e) adapts handheld microprocessor unit 12 for displaying information or instructions from a healthcare professional that are coupled to data management unit 10 from a remote computing facility 54. The manner in which the arrangement of FIGURE 1 implements the above-mentioned functions and others can be better understood with reference to FIGURES 2 and 3.

**[0036]** Referring first to FIGURE 2, clearinghouse 54 receives data from a plurality of self-care microprocessor-based healthcare systems of the type shown in FIGURE 1, with the individual self-care health monitoring systems being indicated in FIGURE 2 by reference numeral 58. Preferably, the data supplied to clearinghouse 54 by each individual self-care health monitoring system 58 consists of "raw data," i.e., test results and related data that was stored in memory circuits of data management unit 10, without further processing by data management unit 10. For example, with respect to the arrangement shown in FIGURE 1, blood glucose test results and associated data such as food intake information, medication dosage and other such conditions are transmitted to clearinghouse 54 and stored with a digitally encoded signal that identifies both the source of the information (i.e., the system user or patient)



and those having access to the stored information (i.e., the system user's doctor or other healthcare professional).

[0037] As shall be recognized upon understanding the manner in which it operates, clearinghouse 54 can be considered to be a central server for the various system users (58 in FIGURE 2) and each healthcare professional 60. In that regard, clearinghouse 54 includes conventionally arranged and interconnected digital processing equipment (represented in FIGURE 2 by digital signal processor 57) which receives digitally encoded information from a user 58 or healthcare professional 60; processes the information as required; stores the information (processed or unprocessed) in memory if necessary; and, transmits the information to an intended recipient (i.e., user 58 or healthcare professional 60).

[0038] In FIGURE 2, rectangular outline 60 represents one of numerous remotely located healthcare professionals who can utilize clearinghouse 54 and the arrangement described relative to FIGURE 1 in monitoring and controlling patient healthcare programs. Shown within outline 60 is a computer 62 (e.g., personal computer), which is coupled to clearinghouse 54 by means of a modem (not shown in FIGURE 2) and a telephone line 64. Also shown in FIGURE 2 is the previously mentioned facsimile machine 55, which is coupled to clearinghouse 54 by means of a second telephone line 68. Using the interface unit of computer 62 (e.g., a keyboard or pointing device such as a mouse), the healthcare professional can establish data communication between computer 62 and clearinghouse 54 via telephone line 64. Once data communication is established between computer 62 and clearinghouse 54, patient information can be obtained from clearinghouse 54 in a manner similar to the manner in which subscribers to various database services access and obtain information. In particular, the healthcare professional can transmit an authorization code to clearinghouse 54 that identifies the healthcare professional as an authorized user of the clearinghouse and, in addition, can transmit a signal representing the patient for which healthcare information is being sought. As is the case with conventional database services and other arrangements, the identifying data is keyed into computer 62 by means of a conventional keyboard (not shown in FIGURE 2) in response to prompts that are generated at clearinghouse 54 for display by the display unit of computer 62 (not shown in FIGURE 2).

[0039] Depending upon the hardware and software arrangement of clearinghouse 54 and selections made by the healthcare professional via computer 62, patient information can be provided to the healthcare professional in different ways. For example, computer 62 can be operated to access data in the form that it is stored in the memory circuits of clearinghouse 54 (i.e., raw data that has not been processed or altered by the computational or data processing arrangements of clearinghouse 54). Such data can be processed, analyzed, printed and/or displayed by computer 62 using commercially available or custom software. On the other hand, various types of analyses may be performed by clearinghouse 54 with the results of the analyses being transmitted to the remotely located healthcare professional 60. For example, clearinghouse 54 can process and analyze data in a manner identical to the processing and analysis provided by the self-care monitoring system of FIGURE 1. With respect to such processing and any other analysis and processing provided by clearinghouse 54, results expressed in alphanumeric format can be sent to computer 62 via telephone line 64 and the modem associated with computer 62, with conventional techniques being used for displaying and/or printing the alphanumeric material for subsequent reference.

[0040] The arrangement of FIGURE 2 also allows the healthcare professional to send messages and/or instructions to each patient via computer 62, telephone line 64, and clearinghouse 54. In particular, clearinghouse 54 can be programmed to generate a menu that is displayed by computer 62 and allows the healthcare professional to select a mode of operation in which information is to be sent to clearinghouse 54 for subsequent transmission to a user of the system described relative to FIGURE 1. This same menu (or related submenus) can be used by the healthcare professional to select one or more modes of operation of the above-described type in which either unmodified patient data or the results of data that has been analyzed by clearinghouse 54 is provided to the healthcare provider via computer 62 and/or facsimile machine 55.

[0041] In the currently contemplated arrangements, operation of the arrangement of FIGURE 2 to provide the user of the invention with messages or instructions such as changes in medication or other aspects of the healthcare program is similar to the operation that allows the healthcare professional to access data sent by a patient, i.e., transmitted to clearinghouse 54 by a data management unit 10 of FIGURE 1. The process differs in that the healthcare professional enters the desired message or instruction via the keyboard or other interface unit of computer 62. Once the data is entered and transmitted to clearinghouse 54, it is stored for subsequent transmission to the user for whom the information or instruction is intended.

[0042] With respect to transmitting stored messages or instructions to a user of the invention, at least two techniques are available. The first technique is based upon the manner in which operational modes are selected in the practice of the invention. Specifically, in the currently preferred embodiments of the invention, program instructions that are stored in data management unit 10 and program cartridge 42 cause the system of FIGURE 1 to generate menu screens which are displayed by display unit 28 of handheld microprocessor unit 12. The menu screens allow the system user to select the basic mode in which the system of FIGURE 1 is to operate and, in addition, allow the user to select operational subcategories within the selected mode of operation. Various techniques are known to those skilled in the art for displaying and selecting menu items. For example, in the practice of this invention,

one or more main menus can be generated and displayed which allow the system user to select operational modes that may include: (a) a monitor mode (e.g., monitoring of blood glucose level); (b) a display mode (e.g., displaying previously obtained blood glucose test results or other relevant information); (c) an input mode (e.g., a mode for entering data such as providing information that relates to the healthcare regimen, medication dosage, food intake, etc.); and, (d) a communications mode (for establishing a communication link between data management unit 10 and personal computer 48 of FIGURE 1; or between data management unit 10 and a remote computing facility such as clearinghouse 54 of FIGURE 2).

**[0043]** In embodiments of the invention that employ a compact video game system for handheld microprocessor unit 12, the selection of menu screens and the selection of menu screen items preferably is accomplished in substantially the same manner as menu screens and menu items are selected during the playing of a video game. For example, the program instructions stored in data management unit 10 and program cartridge 42 of the arrangement of FIGURE 1 can be established so that a predetermined one of the compact video game switches (e.g., switch 32 in FIGURE 1) allows the system user to select a desired main menu in the event that multiple main menus are employed. When the desired main menu is displayed, operation by the user of control pad 30 allows a cursor or other indicator that is displayed on the menu to be positioned adjacent to or over the menu item to be selected. Activation of a switch (e.g., switch 36 of the depicted handheld microprocessor unit 12) causes the handheld microprocessor unit 12 and/or data management unit 10 to initiate the selected operational mode or, if selection of operational submodes is required, causes handheld microprocessor unit 12 to display a submenu.

**[0044]** In view of the above-described manner in which menus and submenus are selected and displayed, it can be recognized that the arrangement of FIGURE 1 can be configured and arranged to display a menu or submenu item that allows the user to obtain and display messages or instructions that have been provided by a healthcare professional and stored in clearinghouse 54. For example, a submenu that is generated upon selection of the previously mentioned communications mode can include submenu items that allow the user to select various communication modes, including a mode in which serial data communication is established between data management unit 10 and clearinghouse 54 and data management unit 10 transmits a message status request to clearinghouse 54. When this technique is used, the data processing system of clearinghouse 54 is programmed to search the clearinghouse memory to determine whether a message exists for the user making the request. Any messages stored in memory for that user are then transmitted to the user and processed for display on display unit 28 of handheld microprocessor unit 12. If no messages exist, clearinghouse 54 transmits a signal that causes display unit 28 to indicate "no messages." In this arrangement, clearinghouse 54 preferably is programmed to store a signal indicating that a stored message has been transmitted to the intended recipient (user). Storing such a signal allows the healthcare professional to determine that messages sent to clearinghouse 54 for forwarding to a patient have been transmitted to that patient. In addition, the program instructions stored in data management unit 10 of FIGURE 1 preferably allow the system user to designate whether received messages and instructions are to be stored in the memory of data management unit 10 for subsequent retrieval or review. In addition, in some instances it may be desirable to program clearinghouse 54 and data management unit 10 so that the healthcare professional can designate (i.e., flag) information such as changes in medication that will be prominently displayed to the user (e.g., accompanied by a blinking indicator) and stored in the memory of data management unit 10 regardless of whether the system user designates the information for storage.

**[0045]** A second technique that can be used for forwarding messages or instructions to a user does not require the system user to select a menu item requesting transmission by clearinghouse 54 of messages that have been stored for forwarding to that user. In particular, clearinghouse 54 can be programmed to operate in a manner that either automatically transmits stored messages for that user when the user operates the system of FIGURE 1 to send information to the clearinghouse or programmed to operate in a manner that informs the user that messages are available and allows the user to access the messages when he or she chooses to do so.

**[0046]** Practicing the invention in an environment in which the healthcare professional uses a personal computer in some or all of the above-discussed ways can be very advantageous. On the other hand, the invention also provides healthcare professionals timely information about system users without the need for a computer (62 in FIGURE 2) or any equipment other than a conventional facsimile machine (55 in FIGURES 1 and 2). Specifically, information provided to clearinghouse 54 by a system user 58 can be sent to a healthcare professional 60 via telephone line 68 and facsimile machine 55, with the information being formatted as a standardized graphic or textual report (56 in FIGURE 1). Formatting a standardized report 56 (i.e., analyzing and processing data supplied by blood glucose monitor 16 or other system monitor or sensor) can be effected either by data management unit 10 or within the clearinghouse facility 54. Moreover, various standardized reports can be provided (e.g., the textual and graphic displays discussed below relating to FIGURES 6-10). Preferably, the signal processing arrangement included in clearinghouse 54 allows each healthcare professional 60 to select which of several standardized reports will be routinely transmitted to the healthcare professionals' facsimile machine 55, and, to do so on a patient-by-patient (user-by-user) basis.

[0047] FIGURE 3 illustrates the manner in which data management unit 10 is arranged and interconnected with other system components for effecting the above-described operational aspects of the invention and additional aspects that are described relative to FIGURES 4-10. As is symbolically indicated in FIGURE 3, handheld microprocessor unit 12 and blood glucose monitor 16 are connected to a dual universal asynchronous receiver transmitter 70 (e.g., by cables 14 and 18 of FIGURE 1, respectively). As also is indicated in FIGURE 3 when a system user connects a personal computer 48 (or other programmable digital signal processor) to data port 44, signal communication is established between personal computer 48 and a second dual universal asynchronous receiver transmitter 72 of data management unit 10. Additionally, dual universal asynchronous receiver transmitter 72 is coupled to modem 46 so that data communication can be established between data management unit 10 and a remote clearinghouse 54 of FIGURES 1 and 2.

[0048] Currently preferred embodiments of data management unit 10 include a plurality of signal sensors 74, with an individual signal sensor being associated with each device that is (or may be) interconnected with data management unit 10. As previously discussed and as is indicated in FIGURE 3, these devices include handheld microprocessor unit 12, blood glucose monitor 16, personal computer 48, remote computing facility 54 and, in addition, peak-flow meter 20 or other additional monitoring devices 22. Each signal sensor 74 that is included in data management unit 10 is electrically connected for receiving a signal that will be present when the device with which that particular signal sensor is associated is connected to data management unit 10 and, in addition, is energized (e.g., turned on). For example, in previously mentioned embodiments of the invention in which data port 44 is an RS-232 connection, the signal sensor 74 that is associated with personal computer 48 can be connected to an RS-232 terminal that is supplied power when a personal computer is connected to data port 44 and the personal computer is turned on. In a similar manner, the signal sensor 74 that is associated with clearinghouse 54 can be connected to modem 46 so that the signal sensor 74 receives an electrical signal when modem 46 is interconnected to a remote computing facility (e.g., clearinghouse 54 of FIGURE 2) via a telephone line 50.

[0049] In the arrangement of FIGURE 3, each signal sensor 74 is a low power switch circuit (e.g., a metal-oxide semiconductor field-effect transistor circuit), which automatically energizes data management unit 10 whenever any one (or more) of the devices associated with signal sensors 74 is connected to data management unit 10 and is energized. Thus, as is indicated in FIGURE 3 by signal path 76, each signal sensor 74 is interconnected with power supply 78, which supplies operating current to the circuitry of data management unit 10 and typically consists of one or more small batteries (e.g., three AAA alkaline cells).

[0050] The microprocessor and other conventional circuitry that enables data management unit 10 to process system signals in accordance with stored program instructions is indicated in FIGURE 3 by central processing unit (CPU) 80. As is indicated in FIGURE 3 by interconnection 82 between CPU 80 and battery 78, CPU 80 receives operating current from power supply 78, with power being provided only when one or more of the signal sensors 74 are activated in the previously described manner. A clock/calendar circuit 84 is connected to CPU 80 (via signal path 86 in FIGURE 3) to allow time and date tagging of blood glucose tests and other information. Although not specifically shown in FIGURE 3, operating power is supplied to clock/calendar 84 at all times.

[0051] In operation, CPU 80 receives and sends signals via a data bus (indicated by signal path 88 in FIGURE 3) which interconnects CPU 80 with dual universal asynchronous receiver transmitters 70 and 72. The data bus 88 also interconnects CPU 80 with memory circuits which, in the depicted embodiment, include a system read-only memory (ROM) 90, a program random access memory (RAM) 92, and an electronically erasable read-only memory (EEROM) 94. System ROM 90 stores program instructions and any data required in order to program data management unit 10 so that data management unit 10 and a handheld microprocessor unit 12 that is programmed with a suitable program cartridge 72 provide the previously discussed system operation and, in addition, system operation of the type described relative to FIGURES 4-10. During operation of the system, program RAM 92 provides memory space that allows CPU 80 to carry out various operations that are required for sequencing and controlling the operation of the system of FIGURE 1. In addition, RAM 92 can provide memory space that allows external programs (e.g., programs provided by clearinghouse 54) to be stored and executed. EEROM 94 allows blood glucose test results and other data information to be stored and preserved until the information is no longer needed (i.e., until purposely erased by operating the system to provide an appropriate erase signal to EEROM 94).

[0052] FIGURES 4-10 illustrate typical screen displays that are generated by the arrangement of the invention described relative to FIGURES 1-3. Reference will first be made to FIGURES 4 and 5, which exemplify screen displays that are associated with operation of the invention in the blood glucose monitoring mode. Specifically, in the currently preferred embodiments of the invention, blood glucose monitor 16 operates in conjunction with data management unit 10 and handheld microprocessor unit 12 to: (a) perform a test or calibration sequence in which tests are performed to confirm that the system is operating properly; and, (b) perform the blood glucose test sequence in which blood glucose meter 16 senses the user's blood glucose level. Suitable calibration procedures for blood glucose monitors are known in the art. For example, blood glucose monitors often are supplied with a "code strip," that is inserted in the monitor and results in a predetermined value being displayed and stored in memory at the

conclusion of the code strip calibration procedure. When such a code strip calibration procedure is used in the practice of the invention, the procedure is selected from one of the system menus. For example, if the system main menu includes a "monitor" menu item, a submenu displaying system calibration options and an option for initiating the blood glucose test may be displayed when the monitor menu item is selected. When a code strip option is available and selected, a sequence of instructions is generated and displayed by display screen 28 of handheld microprocessor unit 12 to prompt the user to insert the code strip and perform all other required operations. At the conclusion of the code strip calibration sequence, display unit 28 of handheld microprocessor unit 12 displays a message indicating whether or not the calibration procedure has been successfully completed. For example, FIGURE 4 illustrates a screen display that informs the system user that the calibration procedure was not successful and that the code strip should be inserted again (i.e., the calibration procedure is to be repeated). As is indicated in FIGURE 4, display screens that indicate a potential malfunction of the system include a prominent message such as the "Attention" notation included in the screen display of FIGURE 4.

**[0053]** As previously indicated, the blood glucose test sequence that is employed in the currently preferred embodiment of the invention is of the type in which a test strip is inserted in a receptacle that is formed in the blood glucose monitor. A drop of the user's blood is then applied to the test strip and a blood glucose sensing sequence is initiated. When the blood glucose sensing sequence is complete, the user's blood glucose level is displayed.

**[0054]** In the practice of the invention, program instructions stored in data management unit 10 (e.g., system ROM 90 of FIGURE 3) and program instructions stored in program cartridge 42 of handheld microprocessor unit 12 cause the system to display step-by-step monitoring instructions to the system user and, in addition, preferably result in display of diagnostic messages if the test sequence does not proceed in a normal fashion. Although currently available self-contained microprocessor-based blood glucose monitors also display test instruction and diagnostic messages, the invention provides greater message capacity and allows multi-line instructions and diagnostic messages that are displayed in easily understood language rather than cryptic error codes and abbreviated phraseology that is displayed one line or less at a time. For example, as is shown in FIGURE 5, the complete results of a blood glucose test (date, time of day, and blood glucose level in milligrams per deciliter) can be concurrently displayed by display screen 28 of handheld microprocessor unit 12 along with an instruction to remove the test strip from blood glucose monitor 16. As previously mentioned, when the blood glucose test is complete, the time and date tagged blood glucose test result is stored in the memory circuits of data management unit 10 (e.g., stored in EEPROM 94 of FIGURE 3).

**[0055]** The arrangement shown and described relative to FIGURES 1-3 also is advantageous in that data relating to food intake, concurrent medication dosage and other conditions easily can be entered into the system and stored with the time and date tagged blood glucose test result for later review and analysis by the user and/or his or her healthcare professional. Specifically, a menu generated by the system at the beginning or end of the blood glucose monitoring sequence can include items such as "hypoglycemic" and "hyperglycemic," which can be selected using the switches of handheld microprocessor unit 12 (e.g., operation of control pad 30 and switch 36 in FIGURE 1) to indicate the user was experiencing hypoglycemic or hyperglycemic symptoms at the time of monitoring blood glucose level. Food intake can be quantitatively entered in terms of "Bread Exchange" units or other suitable terms by, for example, selecting a food intake menu item and using a submenu display and the switches of handheld microprocessor 12 to select and enter the appropriate information. A similar menu item - submenu selection process also can be used to enter medication data such as the type of insulin used at the time of the glucose monitoring sequence and the dosage.

**[0056]** As was previously mentioned, program instructions stored in data management unit 10 and program instructions stored in program cartridge 42 of handheld microprocessor unit 12 enable the system to display statistical and trend information either in a graphic or alphanumeric format. As is the case relative to controlling other operational aspects of the system, menu screens are provided that allow the system user to select the information that is to be displayed. For example, in the previously discussed embodiments in which a system menu includes a "display" menu item, selection of the menu item results in the display of one or more submenus that list available display options. For example, in the currently preferred embodiments, the user can select graphic display of blood glucose test results over a specific period of time, such as one day, or a particular week. Such selection results in displays of the type shown in FIGURES 6 and 7, respectively. When blood glucose test results for a single day are displayed (FIGURE 6), the day of the week and date can be displayed along with a graphic representation of changes in blood glucose level between the times at which test results were obtained. In the display of FIGURE 6, small icons identify points on the graphic representation that correspond to the blood glucose test results (actual samples). Although not shown in FIGURE 6, coordinate values for blood glucose level and time of day can be displayed if desired. When the user chooses to display a weekly trend graph (FIGURE 7), the display generated by the system is similar to the display of a daily graph, having the time period displayed in conjunction with a graph that consists of lines interconnecting points that correspond to the blood glucose test results.

[0057] The screen display shown in FIGURE 8 is representative of statistical data that can be determined by the system of FIGURE 1 (using conventional computation techniques) and displayed in alphanumeric format. As previously mentioned, such statistical data and information in various other textual and graphic formats can be provided to a healthcare professional (60 in FIGURE 2) in the form of a standardized report 56 (FIGURE 1) that is sent by clearinghouse 54 to facsimile machine 55. In the exemplary screen display of FIGURE 8, statistical data for blood glucose levels over a period of time (e.g., one week) or, alternatively, for a specified number of monitoring tests is provided. In the exemplary display of FIGURE 8, the system (data management unit 10 or clearinghouse 54) also calculates and displays (or prints) the average blood glucose level and the standard deviation. Displayed also is the number of blood glucose test results that were analyzed to obtain the average and the standard deviation; the number of test results under a predetermined level (50 milligrams per deciliter in FIGURE 8); and the number of blood glucose tests that were conducted while the user was experiencing hypoglycemic symptoms. As previously noted, in the preferred embodiments of the invention, a screen display that is generated during the blood glucose monitoring sequence allows the user to identify the blood sample being tested as one taken while experiencing hyperglycemic or hypoglycemic symptoms and, in addition, allows the user to specify other relevant information such as food intake and medication information.

[0058] The currently preferred embodiments of the invention also allow the user to select a display menu item that enables the user to sequentially address, in chronological order, the record of each blood glucose test. As is indicated in FIGURE 9, each record presented to the system user includes the date and time at which the test was conducted, the blood glucose level, and any other information that the user provided. For example, the screen display of FIGURE 9 indicates that the user employed handheld microprocessor unit 12 as an interface to enter data indicating use of 12.5 units of regular insulin; 13.2 units of "NPH" insulin; food intake of one bread exchange unit; and pre-meal hypoglycemic symptoms.

[0059] Use of data management unit 10 in conjunction with handheld microprocessor unit 12 also allows display (or subsequent generation of a standardized report 56) showing blood glucose test results along with food intake and/or medication information. For example, shown in FIGURE 10 is a daily graph in which blood glucose level is displayed in the manner described relative to FIGURE 6. Related food intake and medication dosage is indicated directly below contemporaneous blood glucose levels by vertical bar graphs.

[0060] It will be recognized by those skilled in the art that the above-described screen displays and system operation can readily be attained with conventional programming techniques of the type typically used in programming microprocessor arrangements. It also will be recognized by those skilled in the art that various other types of screen displays can be generated and, in addition, that numerous other changes can be made in the embodiments described herein without departing from the scope of the invention as defined by the appended claims.

## Claims

1. A self care health monitoring system comprising:

a handheld programmable microprocessor-based unit, said programmable microprocessor-based unit including a display screen and a plurality of switches (30,32,34,36,38), said microprocessor-based unit being connectable in signal communication with a program cartridge (42) or other arrangement that provides program instructions for controlling the operation of said programmable microprocessor-based unit;

monitoring means (16) operable for automatically sensing a condition indicative of a person's physical well-being and for producing digitally encoded signals representative of said condition; and

a microprocessor-based data management unit (10) connectable in signal communication with both said programmable microprocessor-based unit (12) and said monitoring means (16), said microprocessor-based data management unit including a central processing unit (80) and a memory circuit (90), said memory circuit (90) for storing program instructions for controlling the operation of said central processing unit, said central processing unit (80) being responsive to program instructions stored in said memory circuit (90) of said microprocessor-based data management unit (10) for processing said digitally encoded signals supplied by said monitoring means (16) that are representative of said automatically sensed condition, said central processing unit (80) of said data management unit (10) supplying signals representative of said sensed condition to said programmable microprocessor-based unit in response to digitally encoded signals that are supplied to said data management unit (10) by said programmable microprocessor-based unit upon selective operation of at least one of said switches of said programmable microprocessor unit and in which the switches (30,32,34,36,38) of the handheld programmable microprocessor-based unit (12), in operation, are used to select the operating mode of both said data management unit and said handheld microprocessor-based unit.

2. The self-care health monitoring system of claim 1 wherein said microprocessor-based unit is connectable in signal communication with a program cartridge that is adapted to be received within a receptacle in the unit, the program cartridge having stored therein the program instructions for controlling the operation of the programmable microprocessor-based unit.
3. The self-care health monitoring system of claim 1 or claim 2 wherein said programmable microprocessor-based unit is a compact video game system
4. The self-care health monitoring system of claim 3 wherein said central processing unit of said microprocessor-based data management unit causes said signals representative of said automatically sensed condition to be stored in said memory circuit of said data management unit; and wherein said data management unit further includes a modem for transmitting said stored digitally encoded signals representative of said sensed condition to a remotely located healthcare professional.
5. The self-care health monitoring system of claim 4 further comprising a clearinghouse facility for receiving said signals supplied via said modem of said microprocessor-based data management unit, said clearinghouse facility being remotely located from said microprocessor-based data management unit and including digital signal processing means for converting said digitally encoded signal supplied via said modem of said microprocessor-based data management unit into a report that provides information relating to said condition automatically sensed by said monitoring means, said signal processing means of said clearinghouse facility for transmitting a facsimile signal representative of said report to said remotely located healthcare professional.
6. The self-care health monitoring system of claim 1, claim 2 or claim 3 wherein said monitoring means is a blood glucose monitor that produces digitally encoded signals representative of the user's blood glucose level when a sample of the user's blood is deposited on a reagent impregnated region of a test strip that is inserted into a receptacle that is included in said blood glucose monitor.
7. The self-care health monitoring system of claim 1 or claim 6 wherein said central processor unit of said microprocessor-based data management unit causes said signals representative of said sensed condition to be stored in said memory circuit of said data management unit; and wherein said data management unit further includes a modem for transmitting said stored digitally encoded signals representative of said sensed condition to a remotely located healthcare professional.
8. The self-care health monitoring system of claim 7 further comprising a clearinghouse facility for receiving said signals supplied via said modem of said microprocessor-based data management unit, said clearinghouse facility being remotely located from said microprocessor-based data management unit and including digital signal processing means for converting said digitally encoded signal supplied via said modem of said microprocessor-based data management unit into a report that provides information relating to said condition sensed by said monitoring means, said signal processing means of said clearinghouse facility for transmitting a facsimile signal representative of said report to said remotely located healthcare professional.
9. The self-care health monitoring system of claim 3 wherein said program instructions included in said program cartridge of said programmable microprocessor-based unit cause said programmable microprocessor-based unit to display one or more menus on said display unit of said programmable microprocessor-based unit and further operation of said one or more switches of said plurality of switches allows the user of said self-care health monitoring system to control the operation of said programmable microprocessor-based unit and said microprocessor-based data management unit, said operation controlled by said user with said one or more switches including the processing of said digitally encoded signals representative of said sensed condition, the transmission of said digitally encoded signals from said data management unit to said programmable microprocessor-based unit and the display of information on said display unit of said programmable microprocessor-based unit.
10. The self-care health monitoring system of claim 9 wherein said one or more menus displayed on said display unit and further operation of said one or more switches allows the user of said self-care health monitoring system to generate graphic and alphanumeric displays on said display unit of said programmable microprocessor-based unit, said alphanumeric and graphic displays being representative of said signals that are representative of said

sensed condition and stored in said memory circuit of said data management unit.

**Patentansprüche**

5

**1. Selbstversorger-Gesundheitsüberwachungssystem, umfassend:**

10

ein programmierbares, mikroprozessorgesteuertes Handgerät mit einem Anzeigebildschirm und mehreren Schaltern (30, 32, 34, 36, 38) und zur Signalübertragung mit einer Programmkassette (42) oder einer anderen Anordnung verbindbar, die Programmbefehle zum Steuern des Betriebs des programmierbaren mikroprozessorgesteuerten Geräts liefert;

15

eine Überwachungseinrichtung (60), die betreibbar ist zum automatischen Erfassen eines Zustands, der kennzeichnend ist für das körperliche Wohlbefinden einer Person, und zum Erzeugen digital kodierter Signale, die für diesen Zustand repräsentativ sind; und

20

eine mikroprozessorgesteuerte Datenverwaltungseinheit (10), die zur Signalübertragung sowohl mit dem programmierbaren, mikroprozessorgesteuerten Gerät (12) als auch mit der Überwachungseinrichtung (16) verbindbar ist, wobei die mikroprozessorgesteuerte Datenverwaltungseinheit eine zentrale Verarbeitungseinheit (80) und eine Speicherschaltung (90) aufweist, von denen die Speicherschaltung (90) zum Speichern von Programmbefehlen zum Steuern des Betriebs der zentralen Verarbeitungseinheit dient, die zentrale Verarbeitungseinheit (80) auf in der Speicherschaltung (90) der mikroprozessorgesteuerten Datenverwaltungseinheit (10) gespeicherte Programmbefehle anspricht, um die von der Überwachungseinrichtung (16) gelieferten, digital kodierten Signale zu verarbeiten, die repräsentativ sind für den automatisch erfaßten Zustand, die Signalverarbeitungseinheit (80) der Datenverwaltungseinheit (10) Signale, die repräsentativ sind für den erfaßten Zustand, ansprechend auf digital kodierte Signale an das programmierbare, mikroprozessorgesteuerte Gerät (12) liefert, die von dem programmierbaren, mikroprozessorgesteuerten Gerät bei selektiver Betätigung mindestens eines der Schalter des programmierbaren, mikroprozessorgesteuerten Geräts an die Datenverwaltungseinheit (10) geliefert werden, wobei die Schaltung (30, 32, 34, 36, 38) des programmierbaren, mikroprozessorgesteuerten Handgeräts (12) im Betrieb dazu dienen, den Betriebsmodus sowohl der Datenverwaltungseinheit als auch des mikroprozessorgesteuerten Handgeräts auszuwählen.

25

30

35

**2. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 1, bei dem das mikroprozessorgesteuerte Gerät für die Signalübertragung mit einer Programmkassette verbindbar ist, die dazu ausgebildet ist, in einer Aufnahme des Geräts aufgenommen zu werden, wobei in der Programmkassette Programmbefehle zum Steuern des Betriebs des programmierbaren, mikroprozessorgesteuerten Geräts gespeichert sind.**

40

**3. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 1 oder 2, bei dem das programmierbare, mikroprozessorgesteuerte Gerät ein Kompakt-Videospielsystem ist.**

45

**4. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 3, bei dem die zentrale Verarbeitungseinheit der mikroprozessorgesteuerten Datenverwaltungseinheit veranlaßt, daß die für den automatisch erfaßten Zustand repräsentativen Signale in der Speicherschaltung der Datenverwaltungseinheit gespeichert werden, und die Datenverwaltungseinheit außerdem ein Modem aufweist, um die gespeicherten, digital kodierten Daten bezüglich des erfaßten Zustands zu einem sich an einer entfernten Stelle befindlichen Gesundheitspflege-Spezialisten zu übertragen.**

50

**5. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 4, weiterhin umfassend eine Verarbeitungs- und Auswertestelle zum Empfangen der über das Modem der mikroprozessorgesteuerten Datenverwaltungseinheit gelieferten Signale, wobei sich die Verarbeitungs- und Auswertestelle entfernt von der mikroprozessorgesteuerten Datenverwaltungseinheit befindet und eine digitale Signalverarbeitungseinrichtung aufweist zum Umsetzen des über das Modem der mikroprozessorgesteuerten Datenverwaltungseinheit gelieferten, digital kodierten Signals in einen Bericht, der Information über den von der Überwachungseinrichtung automatisch erfaßten Zustand liefert, wobei die Signalverarbeitungseinrichtung der Verarbeitungs- und Auswertestelle dazu dient, ein für den Bericht repräsentatives Faksimilesignal an den entfernt befindlichen Gesundheitspflege-Spezialisten zu senden.**

55

**6. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 1, 2 oder 3, bei dem die**

Überwachungseinrichtung ein Blutzuckerüberwacher ist, der digital kodierte Signale erzeugt, welche repräsentativ sind für den Blutzuckerspiegel des Benutzers, wenn eine Probe des Bluts des Benutzers auf eine mit einem Reagenz imprägnierte Zone eines Teststreifens aufgebracht wird, der in eine Aufnahme eingesetzt ist, die in dem Blutzuckerüberwacher enthalten ist.

5

7. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 1 oder 6, bei dem die zentrale Prozessoreinheit der mikroprozessorgesteuerten Datenverwaltungseinheit die für den erfaßten Zustand repräsentativen Signale dazu bringt, in der Speicherschaltung der Datenverwaltungseinheit gespeichert zu werden, wobei die Datenverwaltungseinheit außerdem ein Modem aufweist, um die für den erfaßten Zustand repräsentativen, digital

10

kodierten gespeicherten Signale zu einem an einer entfernten Stelle befindlichen Gesundheitsvorsorge-Spezialisten zu übertragen.

8. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 7, weiterhin umfassend eine Verarbeitungs- und Auswertestelle zum Empfangen der über das Modem der mikroprozessorgesteuerten Datenverwaltungseinheit gelieferten Signale, wobei die Verarbeitungs- und Auswertestelle entfernt von der mikroprozessorgesteuerten Datenverwaltungseinheit gelegen ist und eine digitale Signalverarbeitungseinrichtung aufweist zum Umsetzen der über das Modem der mikroprozessorgesteuerten Datenverwaltungseinheit gelieferten, digital kodierten Signale in einen Bericht, der Information über den von der Überwachungseinrichtung erfaßten Zustand liefert, wobei die Signalverarbeitungseinrichtung der Verarbeitungs- und Auswertestelle dazu dient, ein für den Bericht repräsentatives Faksimilesignal an den entfernt befindlichen Gesundheitsvorsorge-Spezialisten zu übertragen.

15

20

9. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 3, bei dem die in der Programmkassette des programmierbaren, mikroprozessorgesteuerten Geräts enthaltenen Programmbefehle das programmierbare, mikroprozessorgesteuerte Gerät veranlassen, ein oder mehrere Menüs auf der Anzeigeeinheit des programmierbaren, mikroprozessorgesteuerten Geräts anzuzeigen, und weiterhin die Betätigung des einen oder mehrere Schalter von den mehreren Schaltern dem Benutzer des Selbstversorger-Gesundheitsüberwachungssystems ermöglicht, den Betrieb des programmierbaren, mikroprozessorgesteuerten Geräts und der mikroprozessorgesteuerten Datenverwaltungseinheit zu steuern, wobei der von dem Benutzer mit dem einen oder mit mehreren Schaltern gesteuerte Betrieb die Verarbeitung der für den erfaßten Zustand repräsentativen, digital kodierten Signale, die Übertragung der digital kodierten Signale von der Datenverwaltungseinheit zu dem programmierbaren, mikroprozessorgesteuerten Gerät und die Anzeige von Information auf der Anzeigeeinheit des programmierbaren, mikroprozessorgesteuerten Geräts beinhaltet.

25

30

10. Selbstversorger-Gesundheitsüberwachungssystem nach Anspruch 9, bei dem das eine oder mehrere Menüs, das bzw. die auf der Anzeigeeinheit angezeigt werden, und weiterhin die Betätigung des einen oder mehrerer Schalter dem Benutzer des Selbstversorger-Gesundheitsüberwachungssystems die Möglichkeit bieten, graphische und alphanumerische Anzeigen auf der Anzeigeeinheit des programmierbaren, mikroprozessorgesteuerten Geräts zu generieren, wobei die alphanumerischen und graphischen Anzeigen repräsentativ sind für die erwähnten Signale, die ihrerseits repräsentativ sind für den erfaßten Zustand, und die in der Speicherschaltung der Datenverwaltungseinheit gespeichert sind.

35

40

## Revendications

45

1. Système de contrôle de santé à soins automatiques comprenant :

50

une unité manuelle basée sur un microprocesseur programmable, ladite unité basée sur un microprocesseur programmable incluant un écran d'affichage et une pluralité de commutateurs (30,32,34,36,38), ladite unité basée sur un microprocesseur pouvant être connectée, selon une communication de signaux, à une cartouche de programme (42) ou à un autre agencement qui délivre des instructions de programme pour commander le fonctionnement de ladite unité basée sur un microprocesseur programmable;

55

des moyens de contrôle (16) pouvant agir de manière à détecter automatiquement un état indicatif du bien-être physique d'une personne et produire des signaux codés de façon numérique représentatifs dudit état; et

une unité (10) de gestion de données basée sur un microprocesseur, pouvant être connectée, selon une communication de signaux, avec à la fois ladite unité (12) basée sur un microprocesseur programmable et lesdits moyens de contrôle (16), ladite unité de gestion de données basée sur un microprocesseur incluant une unité centrale de traitement (80) et un circuit de mémoire (90), ledit circuit de mémoire (90) servant à



mémoriser des instructions de programme pour commander le fonctionnement de ladite unité centrale de traitement, ladite unité centrale de traitement (80) étant apte à répondre à des instructions de programme mémorisées dans ledit circuit de mémoire (90) de ladite unité (10) de gestion de données basée sur un microprocesseur pour traiter lesdits signaux codés numériquement envoyés par lesdits moyens de contrôle (16), qui sont représentatifs dudit état détecté automatiquement, ladite unité centrale de traitement (80) de ladite unité (10) de gestion de données délivrant des signaux représentatifs dudit état détecté à ladite unité (12) basée sur un microprocesseur programmable, en réponse à des signaux codés numériquement qui sont envoyés à ladite unité (10) de gestion de données par ladite unité basée sur le microprocesseur programmable lors d'un fonctionnement sélectif d'au moins l'un desdits commutateurs de ladite unité à microprocesseur programmable, et dans lequel les commutateurs (30,32,34,36,38) du microprocesseur programmable manuel (12) en fonctionnement sont utilisés pour sélectionner le mode de fonctionnement à la fois de ladite unité de gestion de données et de ladite unité manuelle basée à microprocesseur.

2. Système de contrôle de santé à soins automatiques selon la revendication 1, dans lequel ladite unité basée sur un microprocesseur peut être connectée, selon une communication de signaux, à une cartouche de programme qui est adaptée pour être logée dans un réceptacle présent dans l'unité, les instructions de programme servant à commander le fonctionnement de l'unité basée sur un microprocesseur programmable étant logées dans la cartouche de programme.
3. Système de contrôle de santé à soins automatiques selon la revendication 1 ou la revendication 2, dans lequel ladite unité basée sur un microprocesseur programmable est un système de jeu vidéo compact.
4. Système de contrôle de santé à soins automatiques selon la revendication 3, dans lequel l'unité centrale de traitement de ladite unité de gestion de données basée sur un microprocesseur déclenche la mémorisation desdits signaux représentatifs dudit état détecté automatiquement dans ledit circuit de mémoire de ladite unité de gestion de données; et dans lequel ladite unité de gestion de données comprend en outre un modem servant à transmettre lesdits signaux codés numériquement et mémorisés, qui sont représentatifs dudit état détecté, à un professionnel de santé situé à distance.
5. Système de contrôle de santé à soins automatiques selon la revendication 4, comprenant en outre une installation de transfert, qui est située à distance de ladite unité de gestion de données basée sur un microprocesseur et incluant des moyens de traitement de signaux numériques pour convertir ledit signal codé numériquement délivré par l'intermédiaire dudit modem de ladite unité de gestion de données basée sur un microprocesseur, en un rapport qui fournit une information concernant ledit état détecté automatiquement par lesdits moyens de contrôle, lesdits moyens de traitement de signaux de ladite installation de transfert servant à transmettre un signal de télécopie représentatif dudit rapport audit professionnel de santé situé à distance.
6. Système de contrôle de santé à soins automatiques selon la revendication 1, la revendication 2 ou la revendication 3, dans lequel lesdits moyens de contrôle sont une unité de contrôle du glucose sanguin, qui produit des signaux codés numériquement représentatifs du niveau de glucose sanguin d'un utilisateur, lorsqu'un échantillon du sang de l'utilisateur est déposé sur une zone imprégnée d'un réactif d'une bande de test qui est insérée dans un réceptacle qui est incluse dans ladite unité de contrôle du glucose sanguin.
7. Système de contrôle de santé à soins automatiques selon la revendication 1 ou la revendication 6, dans lequel ladite unité à processeur centrale de ladite unité de gestion de données basée sur un microprocesseur déclenche la mémorisation desdits signaux représentatifs dudit état détecté automatiquement, dans ledit circuit de mémoire de ladite unité de gestion de données; et dans lequel ladite unité de gestion de données comprend en outre un modem servant à transmettre lesdits signaux codés numériquement et mémorisés, qui sont représentatifs dudit état détecté, à un professionnel de santé situé à distance.
8. Système de contrôle de santé à soins automatiques selon la revendication 7, comprenant en outre une installation de transfert pour recevoir lesdits signaux fournis par l'intermédiaire du modem de ladite unité de gestion de données basée sur un microprocesseur, ladite installation de transfert étant située à distance de ladite unité de gestion de données basée sur un microprocesseur et incluant des moyens de traitement de signaux numériques pour convertir ledit signal codé numériquement délivré par l'intermédiaire dudit modem de ladite unité de gestion de données basée sur un microprocesseur en un rapport qui fournit une information concernant ledit état détecté par lesdits moyens de contrôle, lesdits moyens de traitement de signaux de ladite installation de transfert

servant à transmettre un signal de télécopie représentatif dudit rapport audit professionnel de santé situé à distance.

- 5 9. Système de contrôle de santé à soins automatiques selon la revendication 3, dans lequel lesdites instructions de programme incluses dans ladite cartouche de programme de ladite unité basée sur un microprocesseur programmable amènent ladite unité basée sur un microprocesseur programmable à afficher un ou plusieurs menus dans ladite unité d'affichage de ladite unité basée sur un microprocesseur programmable et un autre actionnement desdits un ou plusieurs commutateurs de ladite pluralité de commutateurs permet à l'utilisateur dudit système de
- 10 contrôle de santé à soins automatiques de contrôler le fonctionnement de ladite unité basée sur un microprocesseur programmable et de ladite unité de gestion de données basée sur un microprocesseur, ladite opération commandée par ledit utilisateur avec ledit un ou plusieurs commutateurs incluant le traitement desdits signaux codés numériquement, qui sont représentatifs dudit état détecté, la transmission desdits signaux codés numériquement depuis ladite unité de gestion de données à ladite unité basée sur un microprocesseur programmable, et l'affichage d'informations sur ladite unité d'affichage de ladite unité basée sur un microprocesseur programmable.
- 15 10. Système de contrôle de santé à soins automatiques selon la revendication 9, dans lequel ledit menu ou ladite pluralité de menus affichés sur ladite unité d'affichage et l'actionnement ultérieur desdits un ou plusieurs commutateurs permet à l'utilisateur dudit système de contrôle de santé à soins automatiques de générer des affichages graphiques et alphanumériques sur ladite unité d'affichage de ladite unité basée sur un
- 20 microprocesseur programmable, lesdits dispositifs d'affichage alphanumérique et graphique étant représentatifs desdits signaux qui sont représentatifs dudit état détecté et sont mémorisés dans ledit circuit de mémoire de ladite unité de gestion de données.
- 25
- 30
- 35
- 40
- 45
- 50
- 55




Fig. 1.




Fig. 2.




Fig. 3.

**Attention**

Calibration was  
not successful.

Please insert  
the code strip  
again.

*Fig.4.*


June 19 12:30 pm

**Blood Glucose**


**109** mg /dl

remove test strip


*Fig.5.*




*Fig.6.*




*Fig.7.*



*Fig. 8.*



*Fig. 9.*



*Fig. 10.*